

OKCT.E92235 - Lampholders, Electric Discharge, 1000 Volts or Less

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Lampholders, Electric Discharge, 1000 Volts or Less

BJB ELECTRIC L P

E92235

6375 ALABAMA HWY

RINGGOLD, GA 30736-2807 United States

Circular fluorescent lamps, four pin, Model(s): 26.739

Circular fluorescent lamps, two pin and four pin, Model(s): 1221, 1222, 26.715, 26.715.4701, 26.715.6701, 26.716, 26.716.4700, 26.716.6700, 26.732, 26.732.8201, 26.735, 26.735.1002, 26.735.1003

Electric discharge lampholders, 1000 v or less, Model(s): 1856, 2020, 2021, 26.607, 26.607.6103, 26.726.4803, 26.726.4804, 26.726.4805, 26.726.4806, 26.726.4807, 26.726.4808, 26.726.4832, 26.726.4840, 26.726.49+, 26.726.6XXX, 26.746+, 26.801

Electric discharge lampholders, 1000 v or less, Model(s): 26.734 , with suffix numbers to denote mounting means.

Electric discharge lampholders, 1000 v or less, compact lamps, four pin, Type 2G11, Model(s): 26.746

Electric discharge lampholders, 1000 v or less, compact lamps, two pin and four pin, Model(s): 1301*, 1302*, 1303*, 1303X*, 1311*, 1323*, 1324*, 1325*, 1326*, 1327*, 1328*, 1329*, 26.719*, 26.720*, 26.721*, 26.723*, 26.725*, 26.726*, 26.727*, 26.727.3303*, 26.727.4301*, 26.727.8501*, 26.727.8502*, 26.730.3301*, 26.730.3303*, 26.730.3306*, 26.745*

Electric discharge lampholders, 1000 v or less, marked T120 indicates temperature rating, Model(s): 26.292.1111, 26.292.1112

Electric discharge lampholders, 1000 v or less, marking HT120 indicates temperature rating, Model(s): 26.290.1011, 26.290.1012, 26.290.5411, 26.290.5412, 26.290.5414, 26.292.1001, 26.292.1002, 26.292.1101, 26.292.1102, 26.292.1411, 26.292.4001, 26.292.4002, 26.292.6001, 26.292.6002, 26.292.6101, 26.292.6102, 26.311.6323

Electric discharge lampholders, 1000 v or less, marking HT120 indicates temperature rating, Model(s): 26.292.6xxx , where xxx is 000-999, except for models 26.292.6101, 26.292.6102, 26.292.6001, and 26.292.6002. May be marked with an I in a circle to indicate instant start.

Electric discharge lampholders, 1000 v or less, may be marked T115 to indicate temperature rating, Model(s): 26.801.1003, 26.801.1004, 26.801.1113, 26.801.1114

Electric discharge lampholders, 1000 v or less, medium bipin, Model(s): 26.253*, 26.255*, 26.272*, 26.290, 26.293*, 26.297, 26.306*, 26.306.4018*, 26.306.4118*, 26.307*, 26.307.4023*, 26.308, 26.310, 26.311*, 26.311.1228*, 26.311.1230*, 26.311.6228*, 26.311.6230*, 26.311.6323*, 26.313, 26.420*, 26.422*, 26.424*, 26.431, 27.240*, 27.241*

Electric discharge lampholders, 1000 v or less, medium bipin with start holders, Model(s): 26.269, 26.280*, 26.291, 26.421*

Electric discharge lampholders, 1000 v or less, medium bipin with start holders, Model(s): 26.280 (XXXX) , where XXXX can be 6421, 6425, 6521, 6525, 6025, 6125

Electric discharge lampholders, 1000 v or less, medium bipin, marked HT115 to indicate temperature rating, Model(s): 26.422.4009, 26.422.4109, 26.422.4309, 26.422.4409

Electric discharge lampholders, 1000 v or less, medium bipin, may be marked T110 to indicate temperature rating,

Model(s): 26.240.U301, 26.241.U301, 26.290.5011, 26.290.5012, 26.290.5013, 26.290.5014, 26.290.6112#, 26.291.4011.50, 26.292.6211#, 26.292.6212#, 26.292.6411#, 26.293, with additional suffixes.#, 26.306.1025, 26.307, with additional suffixes.#, 26.307.1030, 26.308.1028, 26.311.1223, 26.311.6216, 26.422, with additional suffixes.#, 26.422.1113, 26.613.1001, 26.620.2004, 26.620.8924, 26.640.2001, 26.640.2002, 26.640.2003, 26.640.2101, 26.640.2302, 26.641.2001, 26.641.2002, 26.641.2003, 26.641.2004, 26.641.2006, 26.641.2007, 26.641.2101, 26.641.2102, 26.641.2103, 26.641.2104, 26.641.2201, 26.641.2202, 26.641.2203, 26.641.2204, 26.641.2206, 26.641.2301, 26.641.2302, 26.641.2403, 26.641.2404, 26.641.9103, 26.641.9202, 26.641.9203, 26.641.9204, 26.661.2004, 26.662.2001, 26.662.2002, 26.662.3001, 26.662.3002, 26.662.3011

Electric discharge lampholders, 1000 v or less, medium bipin, may be marked T120 to indicate temperature rating,

Model(s): 26.297.3023, 26.297.3123, 26.297.6xxx#, 26.297.7023#, 26.297.7123#, 26.307.6xxx#, 26.313.6016#, 26.313.6023#, 26.422.6xxx#

Electric discharge lampholders, 1000 v or less, medium bipin, may be marked T120 to indicate temperature rating,

Model(s): 26.293.6xxx, where xxx is 000 to 999, except 101 and 102. May be marked with an I in a circle to indicate instant start.

Electric discharge lampholders, 1000 v or less, miniature bipin, Model(s): 2019.24*, 2019.35*, 26.603*, 26.604*, 26.613*, 26.620*, 26.620.2001*, 26.620.2003*, 26.620.2004*, 26.620.2005*, 26.620.2006*, 26.620.2011*, 26.620.2012*, 26.620.2017*, 26.620.2018*, 26.620.2091*, 26.620.2101*, 26.620.2103*, 26.620.2104*, 26.620.2105*, 26.620.2106*, 26.620.2112*, 26.620.2201*, 26.620.2203*, 26.620.2204*, 26.620.2304*, 26.620.3004*, 26.620.3005*, 26.620.3006*, 26.620.4001*, 26.620.4091*, 26.620.4101*, 26.620.4201*, 26.620.4301*, 26.620.9103*, 26.640*, 26.641*, 26.642*, 26.660.1001*, 26.660.1002*, 26.660.2009*, 26.661.2001*, 26.661.2002*, 26.661.2004*, 26.661.2005*, 26.661.2006*, 26.661.2102*, 26.661.2104*, 26.661.2202*, 26.662.2001*, 26.662.2002*, 26.662.2003*, 26.662.2101*, 26.662.2103*, 26.662.2201*, 26.662.9101*

Electric discharge lampholders, 1000 v or less, miniature bipin G5, Model(s): 26.614.1001@, 26.614.1011@, 26.614.2020@, 26.614.2025@, 26.614.3011@, 26.614.3015@, 26.614.3115, 26.614.4115

Protective caps, Model(s): 26.923

- May be marked with an I in a circle to indicate instant start.


#

* - May be followed by additional suffixes as indicated in individual reports.

@ - May be provided with additional suffixes for commercial purposes.

+ - May be followed by suffixes to denote alternate mounting configurations as noted in the sections.

Last Updated on 2022-09-08



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."

OKCT7.E92235 - Lampholders, Electric Discharge, 1000 Volts or Less Certified for Canada

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Lampholders, Electric Discharge, 1000 Volts or Less Certified for Canada

BJB ELECTRIC L P

6375 ALABAMA HWY

RINGGOLD, GA 30736-2807 United States

E92235

Circular fluorescent lamps, four pin, Model(s): 26.739

Circular fluorescent lamps, two pin and four pin, Model(s): 1221, 1222, 26.715, 26.715.4701, 26.715.6701, 26.716, 26.716.4700, 26.716.6700, 26.732, 26.732.8201, 26.735, 26.735.1002, 26.735.1003

Electric discharge lampholders, 1000 v or less, Model(s): 1856, 2020, 2021, 26.607, 26.607.6103, 26.726.4803, 26.726.4804, 26.726.4805, 26.726.4806, 26.726.4807, 26.726.4808, 26.726.4832, 26.726.4840, 26.726.49+, 26.726.6XXX, 26.746+, 26.801

Electric discharge lampholders, 1000 v or less, Model(s): 26.734 , with suffix numbers to denote mounting means.

Electric discharge lampholders, 1000 v or less, compact lamps, four pin, Type 2G11, Model(s): 26.746

Electric discharge lampholders, 1000 v or less, compact lamps, two pin and four pin, Model(s): 1301*, 1302*, 1303*, 1303X*, 1311*, 1323*, 1324*, 1325*, 1326*, 1327*, 1328*, 1329*, 26.719*, 26.720*, 26.721*, 26.723*, 26.725*, 26.726*, 26.727*, 26.727.3303*, 26.727.4301*, 26.727.8501*, 26.727.8502*, 26.730.3301*, 26.730.3303*, 26.730.3306*, 26.745*

Electric discharge lampholders, 1000 v or less, marked T120 indicates temperature rating, Model(s): 26.292.1111, 26.292.1112

Electric discharge lampholders, 1000 v or less, marking HT120 indicates temperature rating, Model(s): 26.290.1011, 26.290.1012, 26.290.5411, 26.290.5412, 26.290.5414, 26.292.1001, 26.292.1002, 26.292.1101, 26.292.1102, 26.292.1411, 26.292.4001, 26.292.4002, 26.292.6001, 26.292.6002, 26.292.6101, 26.292.6102, 26.311.6323

Electric discharge lampholders, 1000 v or less, marking HT120 indicates temperature rating, Model(s): 26.292.6xxx , where xxx is 000-999, except for models 26.292.6101, 26.292.6102, 26.292.6001, and 26.292.6002. May be marked with an I in a circle to indicate instant start.

Electric discharge lampholders, 1000 v or less, may be marked T115 to indicate temperature rating, Model(s): 26.801.1003, 26.801.1004, 26.801.1113, 26.801.1114

Electric discharge lampholders, 1000 v or less, medium bipin, Model(s): 26.253*, 26.255*, 26.272*, 26.290, 26.293*, 26.297, 26.306*, 26.306.4018*, 26.306.4118*, 26.307*, 26.307.4023*, 26.308, 26.310, 26.311*, 26.311.1228*, 26.311.1230*, 26.311.6228*, 26.311.6230*, 26.311.6323*, 26.313, 26.420*, 26.422*, 26.424*, 26.431, 27.240*, 27.241*

Electric discharge lampholders, 1000 v or less, medium bipin with start holders, Model(s): 26.269, 26.280*, 26.291, 26.421*

Electric discharge lampholders, 1000 v or less, medium bipin with start holders, Model(s): 26.280 (XXXX) , where XXXX can be 6421, 6425, 6521, 6525, 6025, 6125

Electric discharge lampholders, 1000 v or less, medium bipin, marked HT115 to indicate temperature rating, Model(s): 26.422.4009, 26.422.4109, 26.422.4309, 26.422.4409

Electric discharge lampholders, 1000 v or less, medium bipin, may be marked T110 to indicate temperature rating, Model(s): 26.240.U301, 26.241.U301, 26.290.5011, 26.290.5012, 26.290.5013, 26.290.5014, 26.290.6112#, 26.291.4011.50, 26.292.6211#, 26.292.6212#, 26.292.6411#, 26.293, with additional suffixes.#, 26.306.1025, 26.307, with additional suffixes.#, 26.307.1030, 26.308.1028, 26.311.1223, 26.311.6216, 26.422, with additional suffixes.#, 26.422.1113, 26.613.1001, 26.620.2004, 26.620.8924, 26.640.2001, 26.640.2002, 26.640.2003, 26.640.2101, 26.640.2302, 26.641.2001, 26.641.2002, 26.641.2003, 26.641.2004, 26.641.2006, 26.641.2007, 26.641.2101, 26.641.2102, 26.641.2103, 26.641.2104, 26.641.2201, 26.641.2202, 26.641.2203, 26.641.2204, 26.641.2206, 26.641.2301, 26.641.2302, 26.641.2403, 26.641.2404, 26.641.9103, 26.641.9202, 26.641.9203, 26.641.9204, 26.661.2004, 26.662.2001, 26.662.2002, 26.662.3001, 26.662.3002, 26.662.3011

Electric discharge lampholders, 1000 v or less, medium bipin, may be marked T120 to indicate temperature rating, Model(s): 26.297.3023, 26.297.3123, 26.297.6xxx#, 26.297.7023#, 26.297.7123#, 26.307.6xxx#, 26.313.6016#, 26.313.6023#, 26.422.6xxx#

Electric discharge lampholders, 1000 v or less, medium bipin, may be marked T120 to indicate temperature rating, Model(s): 26.293.6xxx, where xxx is 000 to 999, except 101 and 102. May be marked with an I in a circle to indicate instant start.

Electric discharge lampholders, 1000 v or less, miniature bipin, Model(s): 2019.24*, 2019.35*, 26.603*, 26.604*, 26.613*, 26.620*, 26.620.2001*, 26.620.2003*, 26.620.2004*, 26.620.2005*, 26.620.2006*, 26.620.2011*, 26.620.2012*, 26.620.2017*, 26.620.2018*, 26.620.2091*, 26.620.2101*, 26.620.2103*, 26.620.2104*, 26.620.2105*, 26.620.2106*, 26.620.2112*, 26.620.2201*, 26.620.2203*, 26.620.2204*, 26.620.2304*, 26.620.3004*, 26.620.3005*, 26.620.3006*, 26.620.4001*, 26.620.4091*, 26.620.4101*, 26.620.4201*, 26.620.4301*, 26.620.9103*, 26.640*, 26.641*, 26.642*, 26.660.1001*, 26.660.1002*, 26.660.2009*, 26.661.2001*, 26.661.2002*, 26.661.2004*, 26.661.2005*, 26.661.2006*, 26.661.2102*, 26.661.2104*, 26.661.2202*, 26.662.2001*, 26.662.2002*, 26.662.2003*, 26.662.2101*, 26.662.2103*, 26.662.2201*, 26.662.9101*

Electric discharge lampholders, 1000 v or less, miniature bipin G5, Model(s): 26.614.1001@, 26.614.1011@, 26.614.2020@, 26.614.2025@, 26.614.3011@, 26.614.3015@, 26.614.3115, 26.614.4115

Protective caps, Model(s): 26.923

- May be marked with an I in a circle to indicate instant start.

#

* - May be followed by additional suffixes as indicated in individual reports.

@ - May be provided with additional suffixes for commercial purposes.

+ - May be followed by suffixes to denote alternate mounting configurations as noted in the sections.

Last Updated on 2022-09-08



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."